REMARKS

By this amendment, Claim 21 has been amended. Hence, Claims 1-67 are pending in this application. The amendment to Claim 21 does not add any new matter to this application. Applicant respectfully submits that the amendment to Claim 21 places Claim 21 in better form for consideration on appeal and the entering of the amendment is therefore respectfully requested.

If there are any additional charges, please charge them to Deposit Account No. 50-1302.

Respectfully submitted,
HICKMAN PALERMO TRUONG & BECKER LLP

Edward A. Becker
Reg. No. 37,777
Date: September 10, 2001

1600 Willow Street
San Jose, CA 95125
(408) 414-1204
Facsimile: (408) 414-1076

CERTIFICATE OF TRANSMISSION
I hereby certify that this correspondence is being facsimile transmitted to the Patent and Trademark Office Fax No. (703) 305-3431
on September 10, 2001 by Sheila Severinghaus

MARKED UP VERSIONS OF CLAIMS

1. (NOT AMENDED) A method for automatically routing an integrated circuit, the method comprising the computer-implemented steps of:

receiving integrated circuit layout data that defines a set of two or more integrated circuit devices to be included in the integrated circuit;

receiving integrated circuit connection data that specifies one or more electrical connections to be made between the integrated circuit devices;

determining, based upon the integrated circuit layout data and the integrated circuit connection data, a set of one or more routing indicators that specify a set of one or more preferable intermediate routing locations through which a routing path is to be located to connect first and second integrated circuit devices from the set of two or more integrated circuit devices;

determining, based upon the integrated circuit layout data, the integrated circuit connection data and the set of one or more routing indicators, the routing path between the first and second integrated circuit devices, wherein the routing path satisfies specified design criteria; and

updating the integrated circuit layout data to generate updated integrated circuit layout data that reflects the routing path between the first and second integrated circuit devices.

2. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path includes determining, based upon the integrated circuit layout data, the integrated circuit connection data, bias direction criteria and straying limit criteria, the routing path between the first and second integrated circuit devices, wherein the bias direction criteria specifies a preferred routing direction for a

routing path between first and second integrated circuit devices from the set of two or more integrated circuit devices and the straying limit criteria defines a routing region in which the routing path between the first and second integrated circuit devices may be placed.

3. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining, based upon the integrated circuit layout data, the integrated circuit connection data and the one or more obstacles, one or more additional routing indicators that specify one or more preferable routing locations through which the routing path is to be located to avoid the one or more obstacles, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more additional routing indicators, the routing path between the first and second integrated circuit devices.

4. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

changing specified straying limit criteria that defines a routing region in which the routing path between the first and second integrated circuit devices may be placed to generate changed specified straying limit criteria that defines a modified routing region, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the changed

specified straying limit criteria, the routing path between the first and second integrated circuit devices.

5. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining a set of one or more layer changes to allow the routing path to avoid the one more obstacles, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of one or more layer changes, the routing path between the first and second integrated circuit devices.

6. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining a set of one or more bends to be included in the routing path to avoid the one more obstacles, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of one or more bends, the routing path between the first and second integrated circuit devices.

7. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining one or more portions of the routing path to be ripped up and rerouted, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more portions of the routing path to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

8. (NOT AMENDED) The method as recited in Claim 7, wherein determining the routing path between the first and second integrated circuit devices further includes

determining one or more portions of one or more other routing paths to be ripped up and rerouted, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators, the one or more portions of the routing path to be ripped up and rerouted and the one or more portions of the one or more other routing paths to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

9. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices further includes

identifying one or more obstacles that block the routing path,

determining one or more portions of one or more other routing paths to be ripped up and rerouted, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or

more portions of the one or more other routing paths to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

10. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes identifying one or more obstacles that block the routing path, and
determining, based upon the integrated circuit layout data, the integrated circuit connection data and the set of one or more routing indicators, the routing path between the first and second integrated circuit devices, wherein the routing path is routed from the second integrated circuit device to the first integrated circuit device.

11. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes identifying one or more obstacles that block the routing path,
determining one or more locations to employ corner clipping to provide additional space for the routing path, and
determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more locations to employ corner clipping, the routing path between the first and second integrated circuit devices.

12. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes identifying one or more obstacles that block the routing path,

determining one or more integrated circuit layout objects to be moved to provide additional space for the routing path, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and moving the one or more integrated circuit layout objects, the routing path between the first and second integrated circuit devices.

13. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes

examining data that indicates whether changes can be made to one or more layout objects defined by the integrated circuit layout data to accommodate the routing of the routing path, and

if the data indicates that changes can be made to the one or more layout objects defined by the integrated circuit layout data to accommodate the routing of the routing path, then

making one or more changes to the one or more layout objects defined by the integrated circuit layout data, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more changes made to the one or more layout objects, the routing path between the first and second integrated circuit devices.

14. (NOT AMENDED) The method as recited in Claim 13, further comprising generating data that specifies the one or more changes made to the one or more layout objects.

15. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes determining a set of one or more routing targets to which the routing path is to be routed, and
determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of one or more routing targets, the routing path between the first and second integrated circuit devices.

16. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes performing one or more design rule checks on one or more portions of the routing path as the routing path is being determined.

17. (NOT AMENDED) The method as recited in Claim 16, further comprising performing a design rule check on the updated integrated circuit layout data, wherein the design rule check does not check one or more layout objects previously checked during determination of the routing path.

18. (NOT AMENDED) The method as recited in Claim 1, wherein determining the routing path between the first and second integrated circuit devices includes extending the routing path a specified amount to generate an extended portion of the routing path, and
selectively performing a design rule check on only the extended portion of the routing path.

19. (NOT AMENDED) The method as recited in Claim 1, wherein all attachment and bend angles defined by the updated integrated circuit layout data are multiples of ninety degrees.

20. (NOT AMENDED) The method as recited in Claim 1, wherein one or more attachment or bend angles defined by the updated integrated circuit layout data are multiples of other than ninety degrees.

21. (ONCE AMENDED) A method for automatically verifying an integrated circuit layout, the method comprising the computer-implemented steps of:

receiving integrated circuit layout data that defines a set of two or more layout objects contained in the integrated circuit layout;

performing a first design rule check on a layout object from the set of two or more layout objects by evaluating the layout object against specified design criteria;

changing one or more values defined by the specified design criteria to generate updated specified design criteria, wherein the changing of the one or more values is performed after a specified amount of time has elapsed and is made with respect to [either] only the layout object; [object or one or more other layout objects from the set of two or more layout objects;] and

performing a second design rule check on the layout object by evaluating the layout object against the updated specified design criteria.

22. (NOT AMENDED) A method for automatically routing an integrated circuit, the method comprising the computer-implemented steps of:

receiving integrated circuit layout data that defines a set of two or more integrated circuit devices to be included in the integrated circuit;

receiving integrated circuit connection data that specifies one or more electrical connections to be made between the integrated circuit devices;

determining, based upon the integrated circuit layout data and the integrated circuit connection data, a set of two or more join points that are to be electrically connected, wherein each join point from the set of two or more join points has an associated set of specified design criteria that control attachment of routing paths thereto;

determining, based upon the integrated circuit layout data and the set of two or more join points, one or more routing paths to connect the set of two or more join points, wherein the one or more routing paths satisfy the specified design criteria associated with the set of two or more join points; and

updating the integrated circuit layout data to generate updated integrated circuit layout data that reflects the one or more routing paths.

23. (NOT AMENDED) A method for automatically routing an integrated circuit, the method comprising the computer-implemented steps of:

receiving integrated circuit layout data that defines a set of two or more integrated circuit devices to be included in the integrated circuit;

receiving integrated circuit connection data that specifies one or more electrical connections to be made between the integrated circuit devices;

determining, based upon the integrated circuit layout data and the integrated circuit connection data, a routing path between first and second integrated circuit devices that satisfies specified design criteria, wherein determining the routing path between the first and second integrated circuit devices includes

determining whether the distance to be routed for a portion of the routing path exceeds a specified distance, and

if the distance to be routed for the portion of the routing path does not exceed the specified distance, then routing the portion of the routing path in a single step; and

updating the integrated circuit layout data to generate updated integrated circuit layout data that reflects the routing path between the first and second integrated circuit devices.

24. (NOT AMENDED) A computer-readable medium carrying one or more sequences of one or more instructions for automatically routing an integrated circuit, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving integrated circuit layout data that defines a set of two or more integrated circuit devices to be included in the integrated circuit;

receiving integrated circuit connection data that specifies one or more electrical connections to be made between the integrated circuit devices;

determining, based upon the integrated circuit layout data and the integrated circuit connection data, a set of one or more routing indicators that specify a set of one or more preferable intermediate routing locations through which a routing path is to be located to connect first and second integrated circuit devices from the set of two or more integrated circuit devices;

determining, based upon the integrated circuit layout data, the integrated circuit connection data and the set of one or more routing indicators, the routing path between the first and second integrated circuit devices, wherein the routing path satisfies specified design criteria; and

updating the integrated circuit layout data to generate updated integrated circuit layout data that reflects the routing path between the first and second integrated circuit devices.

25. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path includes determining, based upon the integrated circuit layout data, the integrated circuit connection data, bias direction criteria and straying limit criteria, the routing path between the first and second integrated circuit devices, wherein the bias direction criteria specifies a preferred routing direction for a routing path between first and second integrated circuit devices from the set of two or more integrated circuit devices and the straying limit criteria defines a routing region in which the routing path between the first and second integrated circuit devices may be placed.

26. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining, based upon the integrated circuit layout data, the integrated circuit connection data and the one or more obstacles, one or more additional routing indicators that specify one or more preferable routing locations through which the routing path is to be located to avoid the one or more obstacles, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more additional routing indicators, the routing path between the first and second integrated circuit devices.

27. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

changing specified straying limit criteria that defines a routing region in which the routing path between the first and second integrated circuit devices may be placed to generate changed specified straying limit criteria that defines a modified routing region, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the changed specified straying limit criteria, the routing path between the first and second integrated circuit devices.

28. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining a set of one or more layer changes to allow the routing path to avoid the one more obstacles, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of one or more layer changes, the routing path between the first and second integrated circuit devices.

29. (NOT AMENDED) A system for automatically routing an integrated circuit, the system comprising:

a data storage mechanism having stored therein

integrated circuit layout data that defines a set of two or more integrated circuit devices to be included in the integrated circuit, and

integrated circuit connection data that specifies one or more electrical connections to be made between the integrated circuit devices; and

a routing mechanism communicatively coupled to the data storage mechanism, the routing mechanism being configured to

determine, based upon the integrated circuit layout data and the integrated circuit connection data, a set of one or more routing indicators that specify a set of one or more preferable intermediate routing locations through which a routing path is to be located to connect first and second integrated circuit devices from the set of two or more integrated circuit devices,

determine, based upon the integrated circuit layout data, the integrated circuit connection data and the set of one or more routing indicators, the routing path between the first and second integrated circuit devices, wherein the routing path satisfies specified design criteria, and

update the integrated circuit layout data to generate updated integrated circuit layout data that reflects the routing path between the first and second integrated circuit devices.

30. (NOT AMENDED) The system as recited in Claim 29, wherein the routing mechanism is further configured to determine the routing path by determining, based upon the integrated circuit layout data, the integrated circuit connection data, bias direction criteria and straying limit criteria, the routing path between the first and second integrated circuit devices, wherein the bias direction criteria

specifies a preferred routing direction for a routing path between first and second integrated circuit devices from the set of two or more integrated circuit devices and the straying limit criteria defines a routing region in which the routing path between the first and second integrated circuit devices may be placed.

31. (NOT AMENDED) The system as recited in Claim 29, wherein the routing mechanism is further configured to determine the routing path between the first and second integrated circuit devices by

identifying one or more obstacles that block the routing path,

determining, based upon the integrated circuit layout data, the integrated circuit connection data and the one or more obstacles, one or more additional routing indicators that specify one or more preferable routing locations through which the routing path is to be located to avoid the one or more obstacles, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more additional routing indicators, the routing path between the first and second integrated circuit devices.

32. (NOT AMENDED) The system as recited in Claim 29, wherein the routing mechanism is further configured to determine the routing path between the first and second integrated circuit devices by

identifying one or more obstacles that block the routing path,

changing specified straying limit criteria that defines a routing region in which the routing path between the first and second integrated circuit devices may be placed to generate changed specified straying limit criteria that defines a modified routing region, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the changed specified straying limit criteria, the routing path between the first and second integrated circuit devices.

33. (NOT AMENDED) The system as recited in Claim 29, wherein routing mechanism is further configured to determine the routing path between the first and second integrated circuit devices by
identifying one or more obstacles that block the routing path,
determining a set of one or more layer changes to allow the routing path to avoid the one more obstacles, and
determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of one or more layer changes, the routing path between the first and second integrated circuit devices.

34. (NOT AMENDED) The method as recited in Claim 1, wherein each routing indicator from the set of one or more routing indicators further specifies a routing direction for the routing path.

35. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes
identifying one or more obstacles that block the routing path,
determining a set of one or more bends to be included in the routing path to avoid the one more obstacles, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of one or more bends, the routing path between the first and second integrated circuit devices.

36. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining one or more portions of the routing path to be ripped up and rerouted, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more portions of the routing path to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

37. (NOT AMENDED) The computer-readable medium as recited in Claim 36, wherein determining the routing path between the first and second integrated circuit devices further includes

determining one or more portions of one or more other routing paths to be ripped up and rerouted, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators, the one or more portions of the routing path to be ripped up and rerouted and the one or more portions of the one or more other routing paths to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

38. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices further includes
identifying one or more obstacles that block the routing path,
determining one or more portions of one or more other routing paths to be ripped up and rerouted, and
determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more portions of the one or more other routing paths to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

39. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes
identifying one or more obstacles that block the routing path, and
determining, based upon the integrated circuit layout data, the integrated circuit connection data and the set of one or more routing indicators, the routing path between the first and second integrated circuit devices, wherein the routing path is routed from the second integrated circuit device to the first integrated circuit device.

40. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes
identifying one or more obstacles that block the routing path,

determining one or more locations to employ corner clipping to provide additional space for the routing path, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more locations to employ corner clipping, the routing path between the first and second integrated circuit devices.

41. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining one or more integrated circuit layout objects to be moved to provide additional space for the routing path, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and moving the one or more integrated circuit layout objects, the routing path between the first and second integrated circuit devices.

42. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes

examining data that indicates whether changes can be made to one or more layout objects defined by the integrated circuit layout data to accommodate the routing of the routing path, and

if the data indicates that changes can be made to the one or more layout objects defined by the integrated circuit layout data to accommodate the routing of the routing path, then

making one or more changes to the one or more layout objects defined by the integrated circuit layout data, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more changes made to the one or more layout objects, the routing path between the first and second integrated circuit devices.

43. (NOT AMENDED) The computer-readable medium as recited in Claim 42, further comprising one or more additional instructions which, when executed by the one or more processors, cause the one or more processors to generate data that specifies the one or more changes made to the one or more layout objects.

44. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes

determining a set of one or more routing targets to which the routing path is to be routed, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of one or more routing targets, the routing path between the first and second integrated circuit devices.

45. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes performing one or more design rule checks on one or more portions of the routing path as the routing path is being determined.

46. (NOT AMENDED) The computer-readable medium as recited in Claim 45, further comprising one or more additional instructions which, when executed by the one or more processors, cause the one or more processors to perform a design rule check on the updated integrated circuit layout data, wherein the design rule check does not check one or more layout objects previously checked during determination of the routing path.

47. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein determining the routing path between the first and second integrated circuit devices includes

extending the routing path a specified amount to generate an extended portion of the routing path, and

selectively performing a design rule check on only the extended portion of the routing path.

48. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein all attachment and bend angles defined by the updated integrated circuit layout data are multiples of ninety degrees.

49. (NOT AMENDED) The computer-readable medium as recited in Claim 24, wherein one or more attachment or bend angles defined by the updated integrated circuit layout data are multiples of other than ninety degrees.

50. (NOT AMENDED) A computer-readable medium carrying one or more sequences of one or more instructions for automatically verifying an integrated circuit layout, the one or more sequences of one or more instructions including

instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving integrated circuit layout data that defines a set of two or more layout objects contained in the integrated circuit layout;

performing a first design rule check on a layout object from the set of two or more layout objects by evaluating the layout object against specified design criteria;

changing one or more values defined by the specified design criteria to generate updated specified design criteria, wherein the changing of the one or more values is performed after a specified amount of time has elapsed and is made with respect to either the layout object or one or more other layout objects from the set of two or more layout objects; and

performing a second design rule check on the layout object by evaluating the layout object against the updated specified design criteria.

51. (NOT AMENDED) A computer-readable medium carrying one or more sequences of one or more instructions for automatically routing an integrated circuit, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving integrated circuit layout data that defines a set of two or more integrated circuit devices to be included in the integrated circuit;

receiving integrated circuit connection data that specifies one or more electrical connections to be made between the integrated circuit devices;

determining, based upon the integrated circuit layout data and the integrated circuit connection data, a set of two or more join points that are to be electrically connected, wherein each join point from the set of two or more

join points has an associated set of specified design criteria that control attachment of routing paths thereto;

determining, based upon the integrated circuit layout data and the set of two or more join points, one or more routing paths to connect the set of two or more join points, wherein the one or more routing paths satisfy the specified design criteria associated with the set of two or more join points; and

updating the integrated circuit layout data to generate updated integrated circuit layout data that reflects the one or more routing paths.

52. (NOT AMENDED) A computer-readable medium carrying one or more sequences of one or more instructions for automatically routing an integrated circuit, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

receiving integrated circuit layout data that defines a set of two or more integrated circuit devices to be included in the integrated circuit;

receiving integrated circuit connection data that specifies one or more electrical connections to be made between the integrated circuit devices;

determining, based upon the integrated circuit layout data and the integrated circuit connection data, a routing path between first and second integrated circuit devices that satisfies specified design criteria, wherein determining the routing path between the first and second integrated circuit devices includes

determining whether the distance to be routed for a portion of the routing path exceeds a specified distance, and

if the distance to be routed for the portion of the routing path does not exceed the specified distance, then routing the portion of the routing path in a single step; and

updating the integrated circuit layout data to generate updated integrated circuit layout data that reflects the routing path between the first and second integrated circuit devices.

53. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes identifying one or more obstacles that block the routing path,

determining a set of one or more bends to be included in the routing path to avoid the one more obstacles, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of one or more bends, the routing path between the first and second integrated circuit devices.

54. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes identifying one or more obstacles that block the routing path,

determining one or more portions of the routing path to be ripped up and rerouted, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more portions of the routing path to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

55. (NOT AMENDED) The system as recited in Claim 54, wherein determining the routing path between the first and second integrated circuit devices further includes

determining one or more portions of one or more other routing paths to be ripped up and rerouted, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators, the one or more portions of the routing path to be ripped up and rerouted and the one or more portions of the one or more other routing paths to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

56. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices further includes

identifying one or more obstacles that block the routing path,

determining one or more portions of one or more other routing paths to be ripped up and rerouted, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more portions of the one or more other routing paths to be ripped up and rerouted, the routing path between the first and second integrated circuit devices.

57. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data and the set of one or more routing indicators, the routing path between the first and second integrated circuit devices, wherein the routing path is routed from the second integrated circuit device to the first integrated circuit device.

58. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining one or more locations to employ corner clipping to provide additional space for the routing path, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more locations to employ corner clipping, the routing path between the first and second integrated circuit devices.

59. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes

identifying one or more obstacles that block the routing path,

determining one or more integrated circuit layout objects to be moved to provide additional space for the routing path, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and moving the one or more integrated circuit layout objects, the routing path between the first and second integrated circuit devices.

60. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes

examining data that indicates whether changes can be made to one or more layout objects defined by the integrated circuit layout data to accommodate the routing of the routing path, and

if the data indicates that changes can be made to the one or more layout objects defined by the integrated circuit layout data to accommodate the routing of the routing path, then

making one or more changes to the one or more layout objects defined by the integrated circuit layout data, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the one or more changes made to the one or more layout objects, the routing path between the first and second integrated circuit devices.

61. (NOT AMENDED) The system as recited in Claim 60, wherein the routing mechanism is further configured to generate data that specifies the one or more changes made to the one or more layout objects.

62. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes

determining a set of one or more routing targets to which the routing path is to be routed, and

determining, based upon the integrated circuit layout data, the integrated circuit connection data, the set of one or more routing indicators and the set of

one or more routing targets, the routing path between the first and second integrated circuit devices.

63. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes performing one or more design rule checks on one or more portions of the routing path as the routing path is being determined.

64. (NOT AMENDED) The system as recited in Claim 63, wherein the routing mechanism is further configured to perform a design rule check on the updated integrated circuit layout data, wherein the design rule check does not check one or more layout objects previously checked during determination of the routing path.

65. (NOT AMENDED) The system as recited in Claim 29, wherein determining the routing path between the first and second integrated circuit devices includes

extending the routing path a specified amount to generate an extended portion of the routing path, and

selectively performing a design rule check on only the extended portion of the routing path.

66. (NOT AMENDED) The system as recited in Claim 29, wherein all attachment and bend angles defined by the updated integrated circuit layout data are multiples of ninety degrees.

67. (NOT AMENDED) The system as recited in Claim 29, wherein one or more attachment or bend angles defined by the updated integrated circuit layout data are multiples of other than ninety degrees.